

# ROTASLASHER HS/R34



A heavy-duty performer, HS 34 is equally suitable for road-side maintenance as for undergrowth clearing. Fitted with clutch protection, this machine is capable of slashing bushes and small trees.

Heavy-duty blades, mounted in hardened journal - swing back if hitting major objects. Universal PTO drive shaft with clutch.

## ROLLERS

Available mounted ex-factory (HSR) or as a separate optional roller/skid kit, HOWARD's rotaslashers with rollers offer additional advantages :

- Totally enclosed cutting chamber, preventing stones, debris, etc. from causing hazards to nearby persons or objects.
- Surface levelling.
- Combined with left and right skids (standard), front and rear rollers ensure a constant cutting height and floating effect. This prevents "scalping" and facilitates neat cutting over kerbs and hollows.



Specification	Working width (cm)	Cutting height (cm)	For tractor (hp)	With Rollers	Weight Kg.
Rotaslasher HS 34/150	150	1-10	55-85	no	300
Rotaslasher HSR 34/150	150	1-10	55-85	yes	340
Rotaslasher HS 34/180	180	1-10	55-85	no	360
Rotaslasher HSR 34/180	180	1-10	55-85	yes	440



## Notes:

Continuous R&D may result in changes of specification for the latest model delivered.  
Howard in ASIA since 1962  
For more details and technical support, please contact your local dealers.

