

# UNIMIX 60/80



Unimix increases soil stability and strength by uniformly mixing fine and coarse materials throughout the entire mixing depth.

On-site stabilising of roadbeds for better bearing load, by fine mixing of soil and gravel with additives, cement, lime, bitumen etc. Interchangeable gears will allow four different rotorspeeds (166-235 rev/min.) Transmission through 1 1/2" pitch drive chain up to 17-ton breaking load. Unimix must be allowed to "float" over obstacles (rock etc.) It is therefore essential that no downward pressure be applied from the tractor hydraulics or lift rods. The implement will by nature of its design work itself down to the workingdepth (max 18 cm) as pre-set via the adjustable sideskids.

Equally useful in establishing a long-lasting laterite farm road - or creating a stabilised roadbed for highways.

Specification	Unimix 60	Unimix 80
Working width, cm	155	205
Working depth, cm	1-18	1-18
Tractor Hp, min.	65	75
3-Point Linkage, Cat.	I/II	I/II
PTO Driveshaft w/clutch	A8	A8
Selectable Mixing Speeds	4	4
Number of Blades	36	48
Weight, Kg.	580	710



*Notes:*

*Continuous R&D may result in changes of specification for the latest model delivered.*

*Howard in ASIA since 1962*

*For more details and technical support, please contact your local dealers.*

